

Standard equipment

- Galvanized tank with manhole 600 mm
- Angle steels with integrated container slide and built in linking point in tank
- Tank content meter against front wall
- Big sight glass at back side
- Pump support between draw bar with vacuum pump Jurop PNE 58 capacity 6200 litres/min
- PTO shaft Walterscheid
- Self-cleaning moisture guard
- Hydraulic shut-off valve at the back 6"
- Side connection 6" with fastener at the left front
- Blind flange 8" at the left front and 6" at the right front
- 4 Metres hose 6" with couplings
- Galvanized mud guards + hose rack
- Double shut-off valves on top
- Cargo Compact hook system excluded



241-901-094



241-901-020



241-902-021



241-901-002-...

Article number	Description	Prices EURO
241-080	Cargo Compact CT 8000	13.405
241-100	Cargo Compact CT 10000	13.915
241-115	Cargo Compact CT 11500	15.930
241-130	Cargo Compact CT 13000	16.790
Available at lower price		
241-901-172	Delivery without vacuum pump	-990
Optional equipment		
241-901-087-001	Coating after galvanising in RAL colour of your choice	3.510
241-901-043	Different dimensions for length and diameter with the same capacity	355
241-901-045	Angle steels with adjustment holes for the complete length of the tank, decreasing in an angle of 2°	1.155
241-901-046-...	Extra blind flange 6"/8" in random position	115
241-901-094	Plastic wheels at the back of the slide	560
241-901-136-002	Pump Jurop PN 84 (1000 RPM) capacity 9000 litres per minute	780
241-901-132-002	Pump Jurop PNE 102 (1000 RPM) capacity 10200 litres per minute	1.105
241-901-133-002	Pump Jurop PNE 122 (1000 RPM) capacity 12200 litres per minute	1.275
241-901-134-002	Pump Jurop PNR 142 (1000 RPM) capacity 14200 litres per minute	2.185
241-901-128-002	Pomp B.P. Star 84/MA (1000 RPM) capaciteit 14800 litre per minuut	1.320
241-901-...-...	Pump 1000 RPM instead of 540 RPM	175
241-901-141-001	Moisture guard with extra security	530
241-901-142-001	Silencer for vacuum pump	470
241-901-004	5 Metres hose 6" instead of 4 metres	110
241-901-005	4 Metres extension hose 6" with male and female coupling	470
241-901-006	4 Metres hose 8" with couplings	470
241-901-139-001	Hydraulic change over for the vacuum pump #	425
241-901-012	Exact distributor with big spreading plate	350
241-901-077-002	Own hydraulic system with Volvo motor and pump (only in comb. with Cargo Compact HS 18000) #	4.940
241-901-062	Shut-off valves on top mounted in front of the tank	355
241-901-002-...	Extra side connection 6" with fastener <input type="radio"/> LF <input type="radio"/> RF <input type="radio"/> LB <input type="radio"/> RB	470
241-901-003-...	Extra side connection 8" with fastener <input type="radio"/> LF <input type="radio"/> RF <input type="radio"/> LB <input type="radio"/> RB	930
241-901-027	Sight tube Ø 150 mm instead of tank content meter, mounted in front wall of the tank	470
241-901-014	Adjusted back side of tank + weld-on parts for Peecon lever sytem	1.260
241-901-152-...	Electro-hydraulic function applicable with options with # - per function	840
Optional equipment for converting loose tanks into container tanks (CT)		
241-901-024	Manhole Ø 600 mm on top of tank	895
241-901-052	Manhole Ø 1100 mm hinging instead of Ø 600 mm	1.195
241-901-079	Sliding fill hatch 600 mm on top of tank hydraulically operated #	1.990
241-901-175	Steps to manhole/sliding fill hatch	475
241-901-020	Complete back wall hydraulically operated, manually locked #	5.815
241-901-021	Complete back wall hydraulically operated, hydraulically locked 2x #	11.625
241-901-022	Fortification rings on the outside of the tank (inside of the tank is completely smooth)	895
241-901-023	Stainless steel slide plate in the tank and fortification rings on the outside of the tank	2.670
241-901-026	Oblong industrial sight glasses - per 4	530

Cargo Compact Loose Container Tanks



Cargo Compact		8000	10000	11500	13000
Volume	m ³	8	10	11,5	13
Total length (A)	mm	5550	5550	5550	5550
Tank diameter (B)	mm	1700	1800	1900	2000
Height tank (C)	mm	2210	2310	2410	2510
Length tank (D)	mm	4500	4530	4590	4600
Weight	kg	2460	2540	2620	2700

