

Standard equipment

- Vertical feed mixer in "Future" version
- 2 Double Action augers with Long-Life serrated cutting knives
- Augers made off high strength steel, thickness 22 mm
- Standard pattern inside tub to increase volume with rubber- or steel extension
- Wireless **Peecon smart control**: controls the hydraulic functions and shows the weight
- 3-point weighingsystem
- Unilateral main bearing
- 2 Adjustable counter knives
- Planetary gearboxes with vertical bearings per auger
- Wear out parts in Hardox 12 mm
- Adjustable towing bracket for high- or lower hitch
- Hydraulic braked axle with parkingbrake
- Standard 2 single mounted integrated wheels 385/65R22,5. As from Biga 24-221/260 Lowliner Future 375/90R22,5 wheels are mounted
- Large transparent sight glasses for inspection of oil level of the gearboxes
- Wide conveyor belt (1000 mm) at the front of the machine
- Platform on both sides accessible with stairs
- Walterscheid PTO shaft with shearing pin security
- Hand-operated support
- Painted in Peecon red
- Observation window for excellent view at the mixing process

Article number	Description	Prices in EURO
147-140-050	Biga 14-197/230 Lowliner Future	41.180
147-160-050	Biga 16-197/230 Lowliner Future	41.535
147-180-050	Biga 18-197/230 Lowliner Future	43.270
147-200-050	Biga 20-197/230 Lowliner Future	44.800
148-240-050	Biga 24-221/260 Lowliner Future	49.030
148-280-050	Biga 28-221/275 Lowliner Future	51.380
Available at lower price		
147-900-353	2 Unloading doors instead of standard wide conveyor belt	-900



Article number	Optional equipment	Prices in EURO
147-900-336	Feedmanagement software and datastick	on demand
147-900-341-...	Extra graphic display at desired position	net price 750
147-900-351	Load sensing (only in combination with electro-hydraulic control)	on demand
147-900-339-002	Rubber tub increase for 2 augers	1.275
147-900-327	Magnet on auger - per auger	810
147-900-149-...	Walterscheid wide angle PTO shaft	435
147-900-340	Air braked axle instead of hydraulic braked axle	1.275
147-900-092	Ball towing eye Scharmüller/Sauerman 80 mm	945
147-900-057	Mounting of battery for weighing in disconnected position	490
147-900-006-...	2 Speed reduction gearbox (standard on Biga 24 and 28 m³ Lowliner Future)	2.450
147-900-122	Operation 2 speed reduction gearbox with Bowden cable from tractor cabin	435
147-900-260	Operation 2 speed reduction gearbox (# incl. el.hydr. operation)	685
147-900-054	Single acting hydraulic support with manual pump	425
147-900-017	Hydraulic support for loading in uncoupled position (# incl. el.hydr. operation)	845
147-900-252	Rear-view camera	565
147-900-321	Bird View (camera system with view on all sides)	net price 1.500
147-900-018-016	Belt conveyor 300 mm hydr. movable to the left and right instead of fixed (# incl. el.hydr. operation)	1.270
147-900-342	Bended conveyor belt to increase the discharge height instead of standard conveyor belt	on demand
147-900-011-...	Extra belt conveyor in height adjustable (L=1150 mm) left/right side, mounted at existing conveyer (# incl. el.hydr.op.)	3.415
147-900-180	Belt conveyor with chain instead of rubber	1.050
147-900-182	Foldable belt conveyor with chain instead of rubber	835
147-900-238	Hydraulically instead of mechanically adjustable counter knives (# incl. el.hydr. operation) - per knife	400
147-900-089-001	Speed regulator for belt conveyor	350
147-900-234	Lighting LED	335
147-900-090	Mineral box	285
147-900-004-002	Potato cutting knife mounted on 2 augers	445
147-900-128-001	Other RAL colour instead of Peecon red	365
147-900-337	Set of magnets for conveyor belt for one side	910
147-900-338	Anti-spill set for unloading door (for Premix)	65
147-900-233	Wear out parts in stainless steel, height 1000 mm and thickness 4 mm	2.935



Biga Lowliner		14-197/230	16-197/230	18-197/230
Length (A)	mm	6950	6990	7050
Width (B)	mm	2480	2480	2480
Height (C)	mm	2420	2640	2780



Biga Lowliner		20-197/230	24-221/260	28-221/275
Length (A)	mm	7110	7690	7780
Width (B)	mm	2480	2750	2750
Height (C)	mm	3100	3120	3360

Biga Lowliner Future

New!

In response to specific requests from the market, Peeters Landbouwmachines developed a machine that stands out on all fronts. The **Biga Lowliner Future** will meet these specific market requirements.

The **Biga Lowliner Future** is a series of 2 auger vertical feed mixers with a low center of gravity where a larger capacity is combined with a low loading height. These models start from 14 m³ up to 28 m³ content. It is a single-axis machine with integrated single wheels. The deep, narrow mixing tub and the sidewall in wide body position in combination with the special augers ensures quick mixing with limited power requirements. It is the ideal machine for mixing round bales and/or rich structured products. The extra thick augers are made of high-strength steel.

The Biga Lowliner Future models are equipped with the new, patented Future mixing tub. They have a wide conveyor belt at the front. Conveyor belts are available in different versions, you can choose for an in height adjustable, a lateral sliding or a banana shaped conveyor belt. Or you can opt for a discharge chain instead of a conveyor belt. The machines will come standard with a smart control handheld for optimal ease of use of your feed mixer.

The **Biga Lowliner Future** provides continuity. Moreover, this machine will ensure homogeneous rations. Thus your livestock will live healthy lives, resulting in optimum yields.



The **Smart Control** can be placed in the tractor or loader for reading the weights, reading level of unloading doors or conveyor height and/or for control of all hydraulic functions. You can also combine functions such as starting the conveyor and opening the unloading door with one simple push on the button. Also the activation of a **Power Booster** is a possibility.

