

Standard equipment Biga Twin Pacman Future

- Patented "Future" mixing tub
- Loading system and silage grab with fixed Long-Life knife
- 2 Double Action augers with Long-Life serrated cutting knives
- Electronic weighing system i-FeedGood L with 4 load cells, suitable for feedmanagement software
- Standard hole pattern inside the tub to increase volume with a rubber extension
- Electro-hydraulic operation for the hydraulic functions
- Walterscheid PTO shaft with shear bolt protection
- 2 Speed reduction gearbox
- Operation reduction gearbox with Bowden cable
- Unilateral main bearing
- 2 Adjustable counter knives
- Planetary drive with spherical bearing per auger
- Large transparent sight glasses for inspection of oil level of the gearboxes
- Central lubrication of the augers
- Chute complete with stainless steel plate at unloading doors
- Perforated platform with stairs
- Single axle with tyres 245/70R19.5 double mounting
- Hydraulic braked axle with hand brake
- Painted in Peecon red and Peecon grey

Article number	Description	Prices in EURO
124-180-058	Biga 18-215 Twin Pacman Future	55.100
Available at lower price		
124-900-013-...	Equipped with 1 instead of 2 unloading doors at the left or right hand side	-530
Optional equipment		
124-900-359-002	Version in accordance with regulation EU 167/2013 Cat. R-a incl. individual RDW examination (incl. air brake, towing bracket and lighting)	3.365
124-900-316	Radiographically display for i-FeedGood	net price 750
124-900-348	Peecon Professional Network feedmanagement software via datastick	1.555
124-900-349	Peecon Professional Network feedmanagement software with wireless connection to pc (1000 m)	3.045
124-900-350	Peecon Business Network feedmanagement software with wireless connection to pc (1000 m)	3.820
124-900-351	Load sensing	on demand
124-900-339-002	Rubber tub increase for 2 augers	1.365
124-900-149-...	Walterscheid wide angle PTO shaft	465
124-900-004-002	Potato cutting knife mounted on 2 augers	480
124-900-121-002	2 Alligator Double Life augers instead of Double Action augers	1.070
124-900-340	Air braked axle instead of hydraulic braked axle	1.365
124-900-005	High hitch with DIN towing bracket	240
124-900-091	Low hitch with pick-up hitch towing bracket and skid food	240
124-900-092	Ball towing eye Scharmüller/Sauerman 80 mm	1.010
124-900-057	Mounting of battery for weighing in disconnected position	525
124-900-054	Single acting hydraulic support with manual pump	455
124-900-017	Hydraulic support for loading in uncoupled position	905
124-900-125-012	Action package: radiographically display, rear-view system with 1 camera and body warmer	net price 950
124-900-178	Output chute with magnets - per unloading door	600
124-900-283	Movable output chutes connected with unloading door - per unloading door	430
124-900-238	Hydraulically instead of mechanically adjustable counter knives - per knife	430
124-900-234	Lighting LED	360
124-900-252	Rear-view camera	605
124-900-090	Mineral box	305
124-900-128-001	Other RAL colour instead of Peecon red	390



<i>Biga Twin Pacman Future</i>		18-215
Capacity	m ³	18
Length (A)	mm	7050
Diameter bottom (D) / Width (B)	mm	2150/2550
Height (C)	mm	3065
Max. cutting height	kg	3700
Loading capacity	kg	7200
Required horsepower	hp	85*
Type of tyres / SA	Continental Goodyear	245/70R19.5 DM

* is required horsepower with reduction gearbox

Biga Twin Pacman Future

The vertical feed mixer **Biga Twin Pacman Future** is equipped with a patented Future mixing tub in combination with a loading system and silage grab. This self-loading machine offers the ultimate user comfort due to its standard built-in rear view camera and electrohydraulic control. The loading mechanism is built robust and completely maintenance free by using a minimum of moving parts. This way a long lifetime is assured. The silage grab has a fixed Longlife knife at the back to give you the cutting capacity you need in any kind of feed. The Future mixing tub provides additional protection against boiling over, especially in the case of dry rations. And thanks to its unique shape, it has extra robustness and stability. By way of a hole pattern, the tub has also been prepared to increase volume with a rubber extension. This way you can enlarge this standard 18 m³ machine up to a volume of 20 m³. As standard the mixer is provided with an electronic weighing system suitable for feedmanagement software.

The **Biga Twin Pacman Future** is equipped with two hydraulically operated unloading doors. The position and the design of these unloading doors will ensure proper dosing of the rations. By adjusting the position of the door, using the indicator, you can determine the quantity to be unloaded. The adjustable discharge chutes have been provided with stainless steel for even better conveyance of the feed. The unique Peecon Double-Action augers ensure fast and homogeneous mixing, conveyance of the feed. The unique Peecon Double-Action augers ensure fast and homogeneous mixing, so that any livestock can be provided with precise and homogeneously mixed rations. The extra thick augers are made from high-tensile steel and has an extra sweeper for an even flow of rations during unloading. Peecon offers modified augers for special products and rations.

The unique auger construction ensure low energy consumption, without compromising the mixing speed. The machine is provided with a separate and robust chassis, which is painted in Peecon grey. And because the load cells completely support the mixing tub, weighing is extremely accurate. The Biga Twin Pacman Future series are provided with straight side walls, which contribute to the perfect mixing of even low-structure rations.

