

# Biga Strawblower



## Standard equipment

- Robust mechanical driven strawblower (1000 RPM) to be mounted on the front- or the backside of the Biga vertical feed mixer. When mounted in the front, the chassis of the Biga will be extended
- Besides mixing you have the possibility to loosen bales and straw them with the same machine
- Round as well as square bales can be processed
- To use on the left and on the right by means of hydraulically rotating blow pipe
- Unique throw rotor with 8 demountable wide throwing paddles ensures a very good dosed output, less chance for jams, easy maintenance
- Wide throwing paddles on a rotor of diameter 1500 mm provide many air movement and a bigger throwing width
- Low blow pipe with hydraulically operated discharge opening
- Hydraulic setting of discharge opening enables adjustable throwing width
- Throwing width up to 20 meters
- 2 Double acting hydraulic functions required # (when the mixer is equipped with electrohydraulic operation, also the strawblower will be operated with this electrohydraulic operation)

Article number	Description	Prices in EURO
...-900-289	Biga Strawblower - Front	11.505
...-900-290	Biga Strawblower - Back	9.600
<b>Optional equipment</b>		
...-900-291	540 RPM instead of 1000 RPM	4.080
...-900-292	Indication for tube rotation (only applicable with Strawblower Back)	425
...-900-304	Spray system with 12 Volt pump, integrated in ring to prevent boiling over, incl. fluid reservoir	2.060