

Biga Strawblower



Standard equipment

- Robust mechanical driven strawblower (1000 RPM) to be mounted on the front- or the backside of the Biga feed mixer. When mounted in the front, the chassis of the Biga will be extended.
- Besides mixing you have the possibility to loosen bales and straw them with the same machine
- Round as well as square bales can be processed
- To use on the left and on the right by means of hydraulically rotating blow pipe
- Unique throw rotor with 8 demountable wide throwing paddles ensure a very good dosed output, less chance for jams and easy maintenance
- Wide throwing paddles on a rotor with a diameter of 1500 mm. This provide many air movement and a bigger throwing width
- Low blow pipe with hydraulically operated discharge opening
- Hydraulic setting of discharge opening enables adjustable throwing width
- Throwing width up to 20 meters
- 2 Double acting hydraulic functions required # (when the mixer is equipped with electrohydraulic operation, also the strawblower will be operated with this electrohydraulic operation)

Article number	Description	Prices in EURO
...-900-289	Biga Strawblower - Front	12.310
...-900-290	Biga Strawblower - Back	10.270
Optional equipment		
...-900-291	540 RPM instead of 1000 RPM	4.365
...-900-292	Indication for tube rotation (applies to the Strawblower - Back)	455
...-900-304	Spray system with 12 Volt pump, integrated in ring to prevent boiling over, incl. fluid reservoir	2.205